

Contact adhesives & accessories

Hranipex adhesives



Hranifix Premium

Hranifix Industry

Hranifix Smart

Technical information

Packing	spray 500 ml; carton (12 pcs) 17; 47.5 kg kegs	17 kg kegs	spray 500 ml; carton (12 pcs) 17; 47.5 kg kegs
Base	polychloroprene	polychloroprene	polychloroprene
Open time in minutes in 20 °C	2 - 5	2 - 5	2 - 5
Solids	38 - 42 %	28 - 34 %	28 - 32 %

Application

By hand, palette-knife, brush or roller	×	×	×
By spraying	•••	•••	•••

Application field

Suitable for the gluing of MDF, DTD, Polyurethane foam, laminates and lots of plastic materials (without plasticizers), ABS, aluminium sheets into most metals and also wood floorings, PVC and other materials. Water resistant contact, high temperature resistance 130°C.

The hose and the gun is advised to be purchased for the application process.

Suitable for the gluing of MDF, DTD, Polyurethane foam, laminates and lots of plastic materials (without plasticizers), ABS, aluminium sheets into most metals and also wood floorings, PVC and other materials. Water resistant contact, high temperature resistance 85°C.

The hose and the gun is advised to be purchased for the application process."

Application field: designed for bonding many substrates including: decorative laminates to particle board, veneers, woods, MDF, plastics (without plasticizers), rubber, upholstery and whole host of other materials. Water resistant, temperature stability 105°C.

The hose and the gun is advised to be purchased for the application process.

Contact adhesives & accessories

Hranipex adhesives



Hranifix DCM Free

Technical information

Packing	spray 500 ml; carton (12 pcs) 17; 47.5 kg kegs
Base	polychloroprene
Open time in minutes in 20 °C	2 - 5
Solids	38 - 42 %

Application

By hand, palette-knife, brush or roller	×
By spraying	•••

Application field

Suitable for bonding wood, particle board, MDF, DTD, polyurethane foam, laminates, cardboard, most plastics (without plasticizers), ABS, aluminium sheeting and most metals, floorings from PVC and other materials. The glued joint is resistant to water and temperatures up to 130 °C. Does not contain Dichloromethane.

The hose and the gun is advised to be purchased for the application process.

Accessories for contact adhesives Hranipex



Hranifix hose 3.6 m

Important tool for correct glue application from keg.



Hranifix gun

Important tool for correct glue application from keg.



Hranifix Pressure rollers

Standard or extended length available.



Hranifix cleaning agent, 17 kg

For cleaning application hoses and pistols.
